

ASSEMBLY INSTRUCTIONS

WindDelta"



1. Insert Spreader into Leading Edge Pockets (Left and Right).

2. Attach the QuikClip® to the Loop on the front of Kite and unwind SkyTails®.





 In stronger winds, tie SkyTails® together for more stability.

## LAUNCHING - ASSISTED LAUNCH

- The kite requires a minimum wind of 8 mph / 11.3 kph. Let out approximately 75 feet / 22.9 m of line and have an assistant hold the kite.
- · With your back to the wind, release the kite and take a few steps backwards, the kite will rise into the air. Tug line to gain altitude, let out line to gain distance.
- · For storage, reverse assembly steps and place into package. Store your kite in a cool dry place. Excessive heat and/or sunlight can damage the package and kite.

## KILE (VEELA

WARNING! Do not fly near overhead power lines.

Keep important information for future reference.

WARNING! Do not use near overhead power lines or during thunderstorms.

WARNING! Not suitable for children under 3 years due to small parts. WARNING! Not suitable for children under 3 years due to long cord. Please remove all packaging material before giving the toy to child. Never fly near an airport.

Never fly over people.

Never fly in thunderstorms.

Never fly near busy streets.

Never fly near overhead power lines.

Never try to retrieve your kite from power lines.

Call your local power company for assistance.